

PHARMACY REFRIGERATION



- Microprocessor controller for precision temperature in the range of 2°C-8°C.
- Audio and visual safety alarm system
- Rust free pre coated steel interior and HIPS plastic for more hygienic use
- Power on delay, time between stops; for more protection
- Ventilated circulation system
- LED lighting and glass door for clear content visibility

Technical Specifications

DESCRIPTION	YC-260WDF	YC-315L	YC-610WDF	YC-810WDF	YC-1200WDF
Capacity(L)	260	315	610	810	1100
Temperature Range (°C)	2-8°C	2-8°C	2-8°C	2-8°C	2-8°C
Refrigerant	R134a	R600a	R290	R290	R290
Cooling method	Ventilated	Air cooling	Ventilated	Ventilated	Ventilated
Display	Digital display	Digital display	Digital display	Digital display	Digital display
Temperature data storage	USB based	USB based	USB based	USB based	USB based
Internal Size(WxDxH) mm	575x612x1695	650x673x1762	1000x610x2020	1190x660x2020	1515x660x2020
Net Weight(Kg)	63	87	122	142	178
Gross Weight (Kg)	68	99	142	165	210
Alarm System	Yes	Yes	Yes	Yes	Yes
Rated Volt/Freq/Power (V/Hz/W)	220/50/180	220/50/220	220/50/310	220/50/390	220/50/490
Inner Material	HIPS	HIPS	Pre-coated steel	Pre-coated steel	Pre-coated steel

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.



Scan QR Code -
Blue Star Customer
Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer
Care Mobile App from
App Store & Google Play



To know more about Blue Star, visit
www.bluestarindia.com, email us at
coolingsolutions@bluestarindia.com
or SMS 'COOL' to 57575

