




Ideal for harsh Indian summers




Adjustable shelves




UV-protected galvanised sheets for interiors & exteriors



Energy efficient cooling unit



Eco-friendly refrigerant



Self-closing door with locking facility

Technical Specifications

		VISICOOLED D SERIES						
		VC65D	VC125D	VC175D	VC250D	VC275D	VC325D	VC590D
Gross Capacity	L	55	130	170	220	250	300	530
Temperature		0°C to +10°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C
Power Supply		230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz
Refrigerant		R600a	R600a	R600a	R600a	R600a	R600a	R290
No of Doors	Nos	1	1	1	1	1	1	2
Provision for Locking		Available	Available	Available	Available	Available	Available	Available
Overall Dimensions (including hinge, castor etc)	mm	445 x 510 x 501	495 x 515 x 1160	495 x 515 x 1280	535 x 520 x 1735	575 x 600 x 1705	615 x 610 x 1790	1000 x 580 x 1855
Net Weight	kg	19	44	46	61	61	64	115
No of Shelves	Nos	Wire /3	Wire /3	Wire/4	Wire/4	Wire/4	Wire/4	Wire/4

		VISICOOLED A SERIES					VISICOOLED E SERIES			FREEZER
		VC95A	VC150A	VC190A	VC290A	VC400A	VC415E	VC750E	VC1250E	VF375E
Gross Capacity	L	95	140	165	285	385	372	657	945	300
Temperature		+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C	-18°C to -22°C
Power Supply		220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz	230V/1Ph/50Hz
Refrigerant		R600a	R600a	R600a	R600a	R600a	R600a	R600a	R290	R404a
No of Doors	Nos	1	1	1	1	1	1	1	2	1
Provision for Locking		Available	Available	Available	Available	Available	Available	Available	Available	Available
Overall Dimensions (including hinge, castor etc)	mm	470x535x812	470x535x1177	500x578x1520	621x688x1709	645x618x1949	595x640x1980	780x705x2080	1200x742x2000	595x640x1965
Net Weight	kg	30.5	35.5	46	59	68	81	123	164	96
No of Shelves	Nos	Wire /2	Wire /3	Wire /3	Wire /3	Wire /4	Wire/5	Wire/5	Wire/5	Wire/6

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.



Scan QR Code - Blue Star Customer Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer Care Mobile App from App Store & Google Play



To know more about Blue Star, visit [www.bluestarindia.com](http://www.bluestarindia.com), email us at [coolingsolutions@bluestarindia.com](mailto:coolingsolutions@bluestarindia.com) or SMS 'COOL' to 57575

